

HYDRO MULCH[®] 2000



- MEETS OR EXCEEDS ALL REQUIREMENTS FOR WOOD FIBER MULCH
- REDUCES SOIL LOSS AND ENHANCES GERMINATION
- CONTAINS 100% GUAR GUM BASED ORGANIC TACKIFIER FOR SUPERIOR EROSION CONTROL PERFORMANCE
- HYDRO MULCH 2000 HOLDS 13.5 TIMES IT'S OWN WEIGHT IN WATER FOR SUPERIOR SEEDLING ESTABLISHMENT
- PREMIXED TACKIFIER ELIMINATES THE EXTRA STEP AND MESS OF FIELD MIXING

DIRECTIONS FOR USE

PLEASE REFER TO EQUIPMENT MANUFACTURER'S LOADING INSTRUCTIONS.



PHYSICAL PROPERTIES

MOISTURE CONTENT	12% +3
ORGANIC CONTENT	96.2% +-8
ASH CONTENT	.8% +-8
GUAR GUM TACKIFIER	3.0% MIN
pH RANGE	4.8 +-2
C FACTOR 2.5:1 SLOPE	.22 (2000 LBS / AC)
WATER HOLDING CAPACITY	1350% MIN

TYPICAL APPLICATION RATE

2.5 TO 1 SLOPE	2000 LBS / AC
2:1 TO 1:1 SLOPE	2500 LBS / AC

PACKAGING

NET WEIGHT 50 LB BALE, 40 BALES PER PALLET

DISTRIBUTED BY

